

VISUAL EXPERIENCE with QUADRATECH DATA SHEET




6.9375" (176mm) Cut-Out Diameter

Front View



3.34" (84.9mm) Mounting Depth (Open Back) **Side View**



3.86" (98mm) Mounting Depth + Enclosure Side View

VXQ68 TECHNICAL SPECIFICATIONS

VXQ68 SKU 66049 - Each

Tweeter 0.75" (19mm) four titanium domes, Ferrofluid-cooled, acoustic back chamber

Woofer 6.5" (165mm) Aluminum cone, Santoprene

surround

Dispersion Technology Quadratech Tweeter with Cymatic Diffuser

40Hz - 20kHz +/-3dB Frequency Response

8 ohms nominal; 6 ohms minimum Impedance Power Handling (RMS) 5 watts minimum; 150 watts maximum

Sensitivity (2.83V/1m) 90dB SPL

Mounting Technology 1-stage, 4 x RotoLock® Clamps Micro Trim Grille (WxH) 8.24" x 12.13" (209.4mm x 308.2mm) 7.88" x 11.77" (200.1mm x 298.9mm) Trimless Grille (WxH)

Speaker Mounting Depth (D) 3.34" (84.9mm) Mounting Depth + Encl. 3.86" (98mm)

Cut-Out Dims (WxH) 6.9375" x 10.75" (176mm x 273mm)

Shipping Weight 10 lbs. (4.5kg)

VXQ 6" RECTANGLE ACCESSORIES

VXQ6-GRILLE-T

6" XPC Micro Trim Rectangle Grille / Each 60483

VXQ6-GRILLE-NT

6" XPC Trimless Rectangle Grille / Each 60484

VXQ6-SE

6" Rectangle Shallow Enclosure / Each 60473

FLEXBRK-6

6" Rectangle Flex Bracket / 5x Pair 92336

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.