


## VISUAL EXPERIENCE with QUADRATECH DATA SHEET



8.25" (210mm) Cut-Out Diameter Front View



3.8" (96.4mm) Mounting Depth (Open Back) Side View



3.92" (99.6mm) Shallow Enclosure **Side View** 



5.92" (150.4mm) Deep Enclosure **Side View** 

## VXQ68R TECHNICAL SPECIFICATIONS

**VXQ68R SKU** 66056 - Each

**Tweeter**0.75" (19mm) four titanium domes,
Ferrofluid-cooled, acoustic back chamber

Woofer 6.5" (165mm) Aluminum cone, Santoprene

surround

**Dispersion Technology** Quadratech Tweeter with Cymatic Diffuser

Frequency Response 40Hz - 20kHz +/-3dB

Impedance8 ohms nominal; 6 ohms minimumPower Handling (RMS)5 watts minimum; 150 watts maximum

Sensitivity (2.83V/1m) 90dB SPL

Mounting Technology 1-stage, 4 x RotoLock® Clamps

Round Micro Trim Grille (Dia)9.64" (244.8mm)Round Trimless Grille (Dia)9.28" (235.6mm)

 Square Micro Trim Grille (WxH)
 9.64" x 9.64" (244.8mm x 244.8mm)

 Square Trimless Grille (WxH)
 9.28" x 9.28" (235.6mm x 235.6mm)

Speaker Mounting Depth (D)3.8" (96.4mm)Mounting Depth + Shallow Encl.3.92" (99.6mm)Mounting Depth + Deep Encl.5.92" (150.4mm)Cut-Out Dims (WxH)8.25" (210mm)Shipping Weight10 lbs. (4.5kg)

## VXQ 6" ROUND ACCESSORIES

VXQ6R-GRILLE-T
6" XPC Micro Trim Round Grille / Each
60477

VXQ6-SE-R
6" Round Shallow Enclosure / Each
VXQ6R-GRILLE-NT
6" XPC Trimless Round Grille / Each
60478

VXQ6-DE-R
6" Round Deep Enclosure / Each

VXQ6SQ-T FLEXBRK

VXQ6SQ-NI

6" XPC Trimless Square Adapter / Each 60490

6" XPC Micro Trim Square Adapter / Each 60489

**FLEXBRK-6-R**6" Round Flex Bracket / 5x Pair 92337

**LIMITED FIVE (5) YEAR WARRANTY** Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.

60468

60469