

VISUAL EXPERIENCE with QUADRATECH DATA SHEET



10.125" (257mm) Cut-Out Diameter Front View



3.78" (96.1mm) Mounting Depth (Open Back) Side View





5.92" (150.4mm) Deep Enclosure **Side View**

VXQ88R TECHNICAL SPECIFICATIONS

VXQ88R SKU 66058 - Each

Tweeter 1" (25mm) four titanium domes, Ferrofluid-cooled, acoustic back chamber

Woofer 8" (203mm) Aluminum cone,

Santoprene surround

Dispersion Technology Quadratech Tweeter with Cymatic Diffuser

Frequency Response 30Hz - 20kHz +/-3dB

Impedance8 ohms nominal; 6 ohms minimumPower Handling (RMS)5 watts minimum; 175 watts maximum

Sensitivity (2.83V/1m) 91dB SPL

Mounting Technology 1-stage, 4 x RotoLock® Clamps

Round Micro Trim Grille (Dia) 11.54" (293.2mm)
Round Trimless Grille (Dia) 11.17" (283.8mm)

 Square Micro Trim Grille (WxH)
 11.54" x 11.54" (293.1mm x 293.1mm)

 Square Trimless Grille (WxH)
 11.18" x 11.18" (283.9mm x 283.9mm)

Speaker Mounting Depth (D) 3.78" (96.1mm)

Mounting Depth + Shallow Encl. (D) 3.92" (99.6mm)

Mounting Depth + Deep Encl. (D) 5.92" (150.4mm)

Cut-Out Dims (Dia) 10.125" (257mm)

Shipping Weight 20.0 lbs. (9.0kg)

VXQ 8" ROUND ACCESSORIES

VXQ8R-GRILLE-T 8" XPC Micro Trim Round Grille / Each	60479	VXQ8-SE-R 8" Round Shallow Enclosure / Each	60470
VXQ8R-GRILLE-NT 8" XPC Trimless Round Grille / Each	60480	VXQ8-DE-R 8" Round Deep Enclosure / Each	60471
VXQ8SQ-T 8" XPC Micro Trim Square Adapter / Each	60491	FLEXBRK-8-R 8" Round Flex Bracket / 5x Pair	92247
VXQ8SQ-NT 8" XPC Trimless Square Adapter / Each	60492		

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.