optomaeurope.com









- Lights on viewing 3600 ANSI Lumens
- Amazing colour bright vivid colours
- Easy connectivity HDMI, USB Power
- Built in audio



## **Specifications**

|--|

EAN: 5055387663695, Colour: B	lack
Display/image	
Display technology	DLP™
Resolution	1080p Full HD (1920x1080)
Brightness	3,600 lumens
Contrast ratio	25,000:1
Native aspect ratio	16:9
	4:3
Aspect ratio - compatible	
Keystone correction - vertical	+/-40°
Uniformity	80%
Screen size	0.71m ~ 7.65m (28" ~ 301") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.47:1 ~ 1.62:1
Projection distance (m)	1m - 9.8m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	15.59mm~17.14mm/0.614"~0.675"
Native offset	116%
	110/0
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
General	
Noise level (typical)	26dB
Noise level (max)	28dB
PC compatibility	
	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz
	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
2D compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
3D compatibility	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
213	
	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
3D Security OSD / display languages	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
Security	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian,
Security	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,
Security	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
Security OSD / display languages	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Security OSD / display languages	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
Security OSD / display languages Operating conditions	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
Security OSD / display languages Operating conditions Remote control	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote
Security OSD / display languages Operating conditions Remote control Speaker count	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power supply	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models Power Power supply Power consumption (standby)	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models <b>Power</b> Power supply Power consumption (standby) Power consumption (min)	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 205W
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models <b>Power</b> Power supply Power consumption (standby) Power consumption (min)	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models <b>Power</b> Power supply Power consumption (standby) Power consumption (min) Power consumption (max)	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 205W
Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Input lag Optional wireless models <b>Power</b> Power consumption (standby) Power consumption (min) Power consumption (max) Weight and dimensions	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 30000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 205W
Security	Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 1 5W AC power cord Remote control 2x AAA batteries Basic user manual 16.00ms WHD200 100 ~ 240V, 50 ~ 60Hz 0.5W 205W 295W







Copyright © 2023, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 19012023011634